

Hitachi Tiered Storage Manager for Mainframe

8.1.0-00 Release Notes

Contents

About this document.....	1
Intended audience.....	1
Getting help	2
About this release	2
Product package contents.....	2
New features and important enhancements.....	2
System requirements.....	2
Resolved problems	4
Known problems	4
Installation precautions.....	4
Usage precautions.....	5
Documentation	6
Abbreviations	6
Conventions: KB and MB	6
Copyrights and licenses.....	6

About this document

This document (RN-92HC208-02, October, 2014) provides late-breaking information about Hitachi Tiered Storage Manager for Mainframe 8.1.0-00. It includes information that was not available at the time the technical documentation for this product was published, as well as a list of known problems and solutions.

Intended audience

This document is intended for customers and Hitachi Data Systems partners who license and use Hitachi Tiered Storage Manager for Mainframe.

Getting help

The Hitachi Data Systems customer support staff is available 24 hours a day, seven days a week. To reach us, please visit the support website at <https://portal.hds.com> for current telephone numbers and other contact information. If you purchased this product from an authorized HDS reseller, contact that reseller for support.

About this release

This release is a major release that adds new features.

Product package contents

Medium	CD-ROM	Revision
Software	Hitachi Tiered Storage Manager for Mainframe	8.1.0-00
Documents	Hitachi Command Suite Tiered Storage Manager for Mainframe User Guide	MK-92HC207-02
	Hitachi Command Suite Tiered Storage Manager for Mainframe Messages	MK-92HC210-02

New features and important enhancements

#	Item	New Features and Enhancements
1	Storage System features	Hitachi Virtual Storage Platform G1000 (VSP G1000) has been supported.
2	Function enhancement	Relocation Priority function has been supported. Priority setting for relocating has been allowed to the DP-VOLs. If relocation priority is enabled for a specific DP-VOL, tier relocation of that DP-VOL is prioritized. VSP G1000 has been supported.
3		Custom Policy has been supported. The setting range of Tiering Policy Level has been extended from 5 to 31. This function avoids excessive allocation to Tier1 or Tier3. VSP G1000 has been supported.

System requirements

Operating system requirements

Refer to "Prerequisites for HTSM for Mainframe" in the Hitachi Tiered Storage Manager for Mainframe User Guide.

#	Operating System
1	z/OS V1R10 - V2R1

Firmware levels

#	Storage system	Required microcode version	Storage System Support Function
1	Hitachi Virtual Storage Platform G1000	80-02-01 or later	0x41 or later
2	Hitachi Virtual Storage Platform	70-06-01-00/00 or later	0x34 or later

Prerequisite programs

Refer to "Prerequisites for HTSM for Mainframe" in the Hitachi Tiered Storage Manager for Mainframe User Guide.

#	Program name	Notes
1	DFSMS™	Standard OS component
2	ISPF	Standard OS component
3	TSO/E	Standard OS component
4	TSO/E REXX	Standard OS component
5	Security Server	To use the resource access control facility (RACF™)
6	IBM™ Library for REXX on zSeries™ Release 4 (FMID HWJ9140) or IBM Library for REXX on zSeries Alternate Library (FMID HWJ9143)	The REXX Alternate Library is included in standard OS component.

Memory and disk space requirements

Refer to "Preparations before using HTSM for Mainframe" in the Hitachi Command Suite Tiered Storage Manager for Mainframe User Guide.

– Virtual memory requirements

The followings indicate the necessary user regions to run HTSM for Mainframe.

- For the user region of 16 MB or less
1,024 KB
- For the extended user region of 16 MB or more
 $4,000 \text{ KB} + (4 \times \text{number of volumes}) \text{ KB}$

– Disk space requirements

Files to be installed	Required space (track)	Number of Directories
HDSKSAMT	15 tracks	5
HDSKLNKT	45 tracks	20
HDSKLPAT	1 track	1

HDSKPRCT	1 track	10
HDSKEXET	5 tracks	10
HDSKEXVT	5 tracks	10
HDSKPNLT	15 tracks	200
HDSKMSGT	1 track	5
HDSKTABT	1 track	5

System requirements have been integrated into the document "Hitachi Command Suite System Requirements" (MK-92HC209). In this document, system requirements are presented in the form of requirements for each type of server, rather than the requirements for individual Hitachi Command Suite products.

Resolved problems

From 8.0.0-00 to 8.1.0-00

#	Resolved problems
1	<p>ISPF operation becomes inoperable and HTSM for MF cannot be terminated.</p> <p>The issue occurs under conditions as follows:</p> <ul style="list-style-type: none"> - When the user SVC is not registered, "ACT" or "DCT" is executed two times on a COMMAND field of the Tiering Policy Group List area. - When the user SVC is not registered, "S", "V" or "P" is executed on a COMMAND field of the Tiering Policy Group List area. - Closing CSV file ends in failure during the KTIMPORT command running.
2	<p>In scanning multiple volumes, the number of detected volumes greater than the actual one is displayed on:</p> <ul style="list-style-type: none"> - The Device Scan Scope panel. - The KTZ032I message.

Known problems

None.

Installation precautions

Refer to "Installation and Setup" in the Hitachi Command Suite Tiered Storage Manager for Mainframe User Guide for full details on the installation of HTSM for Mainframe.

- Before the installation, ensure the required dataset capacity, the number of the directories in the distribution libraries and the target libraries.
- If HTSM for Mainframe and BC Manager exist in the same system, the User SVC in the newer version of either should be registered.

Version description

The main panel displays a version number of this product as follows:

- Version 8.1.0-00

A version displayed in the KTA400I message on the KTDSPENV command is as follows:

- Version 8.1.0-00

A version displayed on the KTENV command is as follows:

- Version 8.1.0-00(02)

A version displayed in the ISPF Setting Information panel and in the YKK001I on the KTINSCHK command is as follows:

- Version 8.1.0-00 (02)

In the "Hitachi Command Suite Tiered Storage Manager for Mainframe User Guide", replace CHKTnnn and Vnnnnnn as follows:

#	In the manual	Replace with
1	CHKTnnn	CHKT806
2	Vnnnnnn	V081000

User SVC version that corresponds to this product version

The User SVC version that corresponds to this product version is as follows:

- Version 7.5.0-00(00) or later

Usage precautions

HTSM for MF and BCM share the same SVC:

- You must compare the version of the currently enabled user SVC registered by Business Continuity Manager and the version of the prerequisite user SVC for Tiered Storage Manager for Mainframe, and then you must use the user SVC of the later version.
 - The prerequisite SVC is 7.5.0 or later.
- To confirm the version of the currently enabled user SVC, use the YKINSCHK command of Business Continuity Manager.
- If the confirmed user SVC version is old and does not satisfy conditions for the prerequisite user SVC version:
 - Use Business Continuity Manager to delete the user SVC, and then use Tiered Storage Manager for Mainframe to register it again.

- If the confirmed user SVC version satisfies conditions for the prerequisite user SVC version:
 - You can use the currently enabled user SVC.

Documentation

Available documents

Document name	Document number	Issue date
Hitachi Command Suite Tiered Storage Manager for Mainframe User Guide	MK-92HC207-02	October, 2014
Hitachi Command Suite Tiered Storage Manager for Mainframe Messages	MK-92HC210-02	October, 2014

Documentation errata

None

Abbreviations

Abbreviation	Full Name
HTSM for Mainframe	Hitachi Tiered Storage Manager for Mainframe
BC Manager	Hitachi Business Continuity Manager
VSP G1000	Hitachi Virtual Storage Platform G1000
VSP	Hitachi Virtual Storage Platform

Conventions: KB and MB

This document uses the following conventions unless otherwise specified:

1 KB (kilobyte) is 1,024 bytes.

1 MB (megabyte) is 1,024² bytes.

Copyrights and licenses

© 2014 Hitachi, Ltd. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or stored in a database or retrieval system for any purpose without the express written permission of Hitachi, Ltd.

Hitachi, Ltd., reserves the right to make changes to this document at any time without notice and assumes no responsibility for its use. This document contains the most current information available at the time of publication. When new or

revised information becomes available, this entire document will be updated and distributed to all registered users.

Some of the features described in this document might not be currently available. Refer to the most recent product announcement for information about feature and product availability, or contact Hitachi, Ltd., at <https://portal.hds.com>.

Notice: Hitachi, Ltd., products and services can be ordered only under the terms and conditions of the applicable Hitachi Data Systems Corporation agreements. The use of Hitachi, Ltd., products is governed by the terms of your agreements with Hitachi Data Systems Corporation.

Hitachi is a registered trademark of Hitachi, Ltd., in the United States and other countries. Hitachi Data Systems is a registered trademark and service mark of Hitachi, Ltd., in the United States and other countries.

Archivas, BlueArc, Essential NAS Platform, HiCommand, Hi-Track, ShadowImage, Tagmaserve, Tagmasoft, Tagmasolve, Tagmastore, TrueCopy, Universal Star Network, and Universal Storage Platform are registered trademarks of Hitachi Data Systems Corporation.

AIX, AS/400, DB2, Domino, DS8.1.00, Enterprise Storage Server, ESCON, FICON, FlashCopy, IBM, Lotus, OS/390, RS6000, S/390, System z9, System z10, Tivoli, VM/ESA, z/OS, z9, zSeries, z/VM, z/VSE are registered trademarks and DS6000, MVS, and z10 are trademarks of International Business Machines Corporation.

All other trademarks, service marks, and company names in this document or website are properties of their respective owners.

Microsoft product screen shots are reprinted with permission from Microsoft Corporation.